

[54] **ENCAPSULATED
ELECTROLUMINESCENCE DEVICE**

[75] **Inventors:** **Kenji Yoshioka; Yasuichi Ono**, both
of Miyagi, Japan

[73] **Assignee:** **Alps Electric Co., Ltd.**, Tokyo, Japan

[21] **Appl. No.:** **311,929**

[22] **Filed:** **Feb. 16, 1989**

[30] **Foreign Application Priority Data**

May 23, 1988 [JP] Japan 63-66787

[51] **Int. Cl.⁵** **H05B 33/04; H05B 33/06**

[52] **U.S. Cl.** **313/506; 313/512;**
350/345

[58] **Field of Search** **313/512, 511, 506;**
350/345

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,509,401 4/1970 Calley, Jr. et al. .

3,514,825 6/1970 Vodicka .

4,721,883 1/1988 Jacobs et al. 313/511 X

FOREIGN PATENT DOCUMENTS

3531736 3/1986 Fed. Rep. of Germany 350/345
3541950 6/1986 Fed. Rep. of Germany 313/512

Primary Examiner—Palmer C. DeMeo

Attorney, Agent, or Firm—Guy W. Shoup; Paul J.
Winters

[57] **ABSTRACT**

An electroluminescence device having an excellent moisture-resistant property is disclosed. Such an electroluminescence device comprises a light emitting layer inserted between an opposite electrode and a transparent electrode to form a multi-layered structure, said structure being airtightly sealed by a pair of protective sheets and said ELD being able to be fitted to an external apparatus by means of a metal fixture. The ELD is characterized in that a metal composite film is formed by inserting a metal foil between a pair of resin films and is used for one of the protective sheets for said opposite electrode. The composite film having a notch which is formed by removing part of the metal foil around a portion of the metal composite film prepared to accommodate the metal fixture.

5 Claims, 2 Drawing Sheets

